



Standard Specification for Commercial Food Waste Pulper and Waterpress Assembly¹

This standard is issued under the fixed designation F 1150; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers commercial pulping and waterpress assemblies intended for grinding of food scraps, paper, cardboard, and disposable plastic food-service ware.

1.2 The values as stated in inch-pound units are to be regarded as the standard. The values in parentheses are given for information only.

1.3 The following safety hazards caveat pertains only to the test method portion, Section 13, of this specification:

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

- A 6 Specification for General Requirements for Rolled Steel Plates, Shapes, Sheet Piling, and Bars for Structural Use²
- A 29 Specification for General Requirements for Steel Bars, Carbon and Alloy, Hot-Wrought and Cold-Finished³
- A 120 Specification for Pipe, Steel, Black and Hot-Dipped, Zinc-Coated (Galvanized), Welded and Seamless, for Ordinary Uses⁴
- A 126 Specification for Gray Iron Castings for Valves, Flanges, and Pipe Fittings⁵
- A 167 Specification for Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip⁶
- A 269 Specification for Seamless and Welded Austenitic Stainless Steel Tubing for General Service⁷
- A 276 Specification for Stainless Steel and Heat-Resisting Steel Bars and Shapes³
- A 436 Specification for Austenitic Gray Iron Castings⁵
- A 505 Specification for General Requirements for Steel and Strip, Alloy, Hot-Rolled and Cold-Rolled⁶

- A 513 Specification for Electric-Resistance-Welded Carbon and Alloy Steel Mechanical Tubing⁷
 - A 519 Specification for Seamless Carbon and Alloy Steel Mechanical Tubing⁷
 - A 532 Specification for Abrasion-Resistant Cast Iron⁵
 - A 554 Specification for Welded Stainless Steel Mechanical Tubing⁷
 - A 582 Specification for Free Machining Stainless and Heat-Resisting Steel Bars; Hot-Rolled or Cold-Finished³
 - A 681 Specification for Alloy Tool Steels³
 - B 43 Specification for Seamless Red Brass Pipe, Standard Sizes⁸
 - B 75 Specification for Seamless Copper Tube⁸
 - D 2000 Classification System for Rubber Products in Automotive Applications⁹
 - D 2287 Specification for NonRigid Vinyl Chloride Polymer and Copolymer Molding and Extrusion Compounds¹⁰
 - D 3915 Specification for Poly(Vinyl Chloride) (PVC) and Related Plastic Pipe and Fitting Compounds¹¹
 - D 3951 Practice for Commercial Packaging¹²
 - E 674 Specification for Industrial Perforated Plate and Screens (Round Opening Series)¹³
 - F 104 Classification System for NonMetallic Gasket Materials¹⁴
 - F 437 Specification for Threaded Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe Fittings, Schedule 80¹⁵
 - F 439 Specifications for Socket-Type Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe Fittings (Schedule 80)¹⁵
 - F 441 Specification for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe, Schedules 40 and 80¹⁵
 - F 442 Specification for Chlorinated Poly(Vinyl Chloride) (CPVC) Plastic Pipe, (SDR-PR)¹⁵
 - F 443 Specification for Bell-End Chlorinated Poly(Vinyl Chloride) (CPVC) Pipe, Schedule 40¹⁵
- 2.2 *Underwriters Laboratory Standards:*¹⁶
- UL 430 Waste Disposers

¹ This specification is under the jurisdiction of ASTM Committee F26 on Food Service Equipment and is the direct responsibility of Subcommittee F26.04 on Mechanical Preparation Equipment.

Current edition approved July 25, 1988. Published September 1988.

² *Annual Book of ASTM Standards*, Vol 01.04.

³ *Annual Book of ASTM Standards*, Vol 01.05.

⁴ Discontinued. See *Annual Book of ASTM Standards*, Vol 01.01.

⁵ *Annual Book of ASTM Standards*, Vol 01.02.

⁶ *Annual Book of ASTM Standards*, Vol 01.03.

⁷ *Annual Book of ASTM Standards*, Vol 01.01.

⁸ *Annual Book of ASTM Standards*, Vol 02.01.

⁹ *Annual Book of ASTM Standards*, Vol 09.01.

¹⁰ *Annual Book of ASTM Standards*, Vol 08.02.

¹¹ *Annual Book of ASTM Standards*, Vol 08.04.

¹² *Annual Book of ASTM Standards*, Vol 15.09.

¹³ *Annual Book of ASTM Standards*, Vol 14.02.

¹⁴ *Annual Book of ASTM Standards*, Vol 09.02.

¹⁵ *Annual Book of ASTM Standards*, Vol 08.04.

¹⁶ Available from Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

UL 508 Electrical Industrial Control Equipment
 2.3 *National Fire Protection Agency Standard*.¹⁷
 NFPA No. 70 National Electric Code

2.4 *Other Publication*:

ASSE Standard No. 1012 Backflow Preventers with Intermediate Atmospheric Vent¹⁸

3. Terminology

3.1 *General*—Commercial pulpers with waterpresses are intended for grinding food waste, food service paper and cardboard products, food service plastic products, documents including computer printouts, general office and retail store paper, and cardboard waste. Materials are ground in a water-filled tank (pulper) to produce a slurry which is then passed to the waterpress to be de-watered. Pulpers are not intended to be used for grinding glass, china, metal, wood, clam, or oyster shells. Any small pieces of metal inadvertently placed in the pulper, such as cardboard box staples, aluminum refreshment cans, or tin food cans, shall be removable from the outside of the pulper tank.

3.2 *Definitions of Terms Specific to This Standard*:

3.2.1 *pulper*—the pulper tank has a motor driven grinding disk to grind and cut waste material, and mixes this material with water to produce a slurry that is pumped to the waterpress through a sizing screen. Pulpers may consist of the following principle parts: tank, motor, grinding disk, particle sizing ring, trash box, legs, feed chute, stationary, and rotating cutters.

3.3 *waterpress*—the waterpress de-waters the slurry generated in the pulper by use of a tapered compression cone and perforated screen, then discharges the pulp down a chute to a waste container. Water removed during this process is pumped to the pulper tank in order to conserve fresh water use. Waterpresses may consist of the following parts: shell, helical transport screw, perforated screen, gearbox, motor, compression cone, discharge housing, chute, and pump.

4. Classification

4.1 *General*—Pulper and waterpress assemblies shall be of the following type, size, and options as specified.

4.2 *Type, Size, and Options* (See Table 1):

4.2.1 *Type A*—Free-standing pulper and waterpress assembly with tray assembly and flanged feet.

4.2.2 *Type B*—Undercounter pulper for 34-in. (86-cm) high counter and waterpress with feed hood and bullet feet.

4.3 All equipment of the same model designation and options on the same purchase order shall have component interchangeability for serviceability.

5. Ordering Information

5.1 Purchasers should select the preferred options permitted in this specification and include the following information in procurement documents:

5.1.1 Title, number, and date of this standard.

¹⁷ Available from the National Fire Protection Agency, Batterymarch Park, Quincy, MA 02269.

¹⁸ Available from American Society of Sanitary Engineering, P.O. Box 9712, Bay Village, OH 44140.

TABLE 1 Type, Size, and Options

Options	Type Pulper with Waterpress	A		B	
	Size Pulper Diameter Inches—Maximum	24	30	24	30
	Pulper Motor HP	5	7.5	5	7.5
	Waterpress Motor HP	2	3	2	3
1	Automatic Shutdown Timer	3	3	3	3
2	18 In. Higher than Standard Waterpress	3	3	3	3
3	Tray Flush (Recirculated Water)	3	3	3	3
4	Trough Flush (Recirculated)	2	2	3	3
5	Single Feed Through Connection	2	2	3	3
6	Double Feed Through Connection	2	2	3	3
7	Feed Hood with Tray	4	4	3	3

- (1) Pulper cover plate supplied in lieu of feed hood.
- (2) Pulper and waterpress type not compatible with optional feature.
- (3) Indicates available option for given type pulper with waterpress.
- (4) Standard for Type A.

5.1.2 Classification of size and type (see Section 4).

5.1.3 Electrical power supply voltage range (see 9.1).

5.1.4 Electrical controls when specified to be remote from the unit (see 9.3).

5.1.5 Optional automatic shutdown timer when specified (see Section 4).

5.1.6 Spare and maintenance parts required.

5.1.7 Optional tray flush uses recycled water from the waterpress when specified (see Section 4).

5.1.8 Optional waterpress for high profile pulp discharge 18 in. above standard height optional when specified (see Section 4).

5.1.9 Optional trough flush when specified (see Section 4).

5.1.10 Optional single feed trough connections on when specified (see Section 4).

5.1.11 Optional double feed trough connections when specified (see Section 4).

5.1.12 Optional feed hood with tray for Type B (see Section 4).

5.1.13 Designate special features required for installation, such as location of controls, location of feed-hood and trough openings, waterpress discharge location, and location for cold water and drain connections.

6. Materials

6.1 Unless otherwise specified, pulpers and waterpresses shall be fabricated of materials specified in documents referenced in Section 2. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or the overall assembly. Unit shall be manufactured for cleanability.

6.1.1 *Corrosion-Resistant Steel*—Shall conform to the requirements of any 300 series steel specified in Specification A 167, Specification A 554, Specification A 276, and Specification A 582.

6.1.2 *Corrosion-Resisting Material*—Corrosion-resisting material is other than corrosion resistant steel that is equivalent in the pulper and waterpress application.

6.1.3 *Abrasion-Resistant Cast Iron*—Shall conform to the requirements specified in Specification A 532.

6.1.4 *Austenitic Gray Iron*—Shall conform to the requirements specified in Specification A 436.

6.1.5 *Copper Tube*—Shall conform to the requirements specified in Specification B 75.

6.1.6 *Brass Pipe*—Shall conform to the requirements specified in Specification B 43.

6.1.7 *Alloy Steel*—Shall conform to the requirements specified in Specifications A 681, A 29, A 6, A 513, A 505, and A 519.

6.1.8 *Black and Galvanized Pipe*—Shall conform to the requirements specified in Specification A 120.

6.1.9 *Gaskets/Seals*—Shall conform to the requirements specified in Specification D 2287, Classification D 2000, and Classification F 104.

6.1.10 *Perforated Metal*—Shall conform to the requirements specified in Specification E 674.

6.1.11 *Stainless Steel Pipe*—Shall conform to the requirements specified in Specification A 269.

6.1.12 *Plastic Piping and Fittings*—Shall conform to the requirements specified in Specifications F 441, A 442, F 443, F 437, F 439, and D 3915.

6.1.13 *Austenitic Gray Iron Pipe Fittings*—Shall conform to the requirements specified in Specification A 126.

7. Design and Construction

7.1 The pulper and waterpress shall be complete, ready for water, waste, and electrical connection. Undercounter units shall be ready for connection to tabling and trough mounting. Optional remote controls shall be complete and ready for wall mount and interconnection to the equipment. The pulper and waterpress shall comply with the requirements of UL 430, 508, and ASSE Standard 1012.

7.2 *Valves*—Flow valves or fresh water solenoid valves, or both, and backflow prevention valves or air gap shall be of corrosion-resistant materials. Solenoid valves shall be fully automatic and suitable for 100°F (37.8°C) water. Manual flow valves or fresh water valves, or both, when provided, shall be of corrosion-resistant materials. Valves shall be suitable for 100°F (37.8°C) water.

7.3 *Tanks*—Tanks shall be of corrosion-resistant steel with minimum sheet metal thickness of 0.070 in. (1.78 mm).

7.4 *Waterpress*—Waterpress enclosure shall be of corrosion-resistant steel with minimum sheet metal wall thickness of 0.070 in. (1.78 mm). Any waterpress frame structure shall be of corrosion-resistant steel or painted carbon steel. Frame material shall be of 0.120-in. minimum thickness. The waterpress screen shall be of 0.059 (1.50 mm) thickness minimum corrosion-resistant perforated steel. Access port for cleaning the screen and a manual cold water screen flush system shall be provided. The waterpress flight screw shall be of corrosion-resistant steel. Thickness of the flight shall be 0.125-in. (3.18-mm) minimum thickness.

7.5 *Pressure Switch*—A pressure switch shall be supplied with each pulper for the purpose of controlling water level in the pulper tank. The switch shall be adjustable.

7.6 *Cutter*—Each pulper shall be supplied with suitable cutters. Cutters shall be of abrasion-resistant iron, tool steel, corrosion-resisting material, or tool steel with carbide cutting edges.

7.7 *Sizing Ring*—Each pulper shall be supplied with a corrosion-resistant steel perforated ring.

7.8 *Pumps*—Shall be of non-ferrous or austenitic gray iron castings. Bearings and motors shall be protected from water contamination by a mechanical shaft seal (see 7.13). Pumps may be direct or belt driven.

7.9 *Gearbox*—Each waterpress flight screw shall be directly driven by a helical or worm gear, single, or double reduction gearbox. The gearbox may be direct or belt driven.

7.10 *Compression Cone*—Waterpress compression cones shall be of corrosion-resistant steel, non-ferrous corrosion-resistant material, or austenitic gray iron casting. The cone shall be tapered to allow gradual de-watering of the pulp.

7.11 *Trash Box*—Each pulper shall be supplied with an externally removable container of corrosion-resistant steel with minimum sheet metal thickness of 0.059 in. (1.50 mm). Minimum usable size of the container shall be 70 in.³.

7.12 *Pulper Disk*—The disk shall be of corrosion-resistant steel with a minimum thickness of 0.218 in. (5.54 mm) with at least 10 carbide cutting teeth attached.

7.13 *Pulper Motor Shaft Seal*—Shall be a water flushed mechanical seal. The seal is to prevent soil and water leakage down the shaft from the pulper to the motor.

7.14 *Motor*—Thermal overload protection shall be provided either on the motor or in the control circuitry.

7.15 *Support Legs*—Pulper and waterpress shall be supported by at least 4 legs, each with bullet or flange feet that can be adjusted, plus or minus 3/4-in. (19 mm) from nominal for leveling the unit. Legs and feet shall be designed for cleanability.

7.16 *Plating, Coating, and Painting*—Pulpers or their individual components shall be plated, coated, or painted for corrosion protection in accordance with the manufacturer's standard practice.

7.17 *Wiring and Circuit Protective Devices*—All wiring and circuit protective devices shall be in accordance with UL 430 or UL 508.

8. Operation Requirements

8.1 Pushing of “fill” button shall fill the system with water. Pushing “start” button shall start the pulper and waterpress motors. Pushing the “stop” button stops all motors and all waver valves close.

9. Electrical Requirements

9.1 The equipment and controls shall meet the requirements of UL 430, U1 508, and NFPA 70. The pulper and waterpress assembly shall operate on one of the following power characteristics specified: (A) 200/60/3; (B) 230/60/3; and (C) 460/60/3.

9.2 *Controls*—All control equipment shall be capable of operation in an ambient room temperature of 115 ± 9°F (46 ± 5°C). “Start-Stop” push buttons shall be mounted in NEMA 12 Controller enclosure.

9.3 *Wiring and Circuit Safety Devices*—All wiring between the machine components shall have provisions for connection at a recognized junction on the machine.

10. Lubrication Requirements

10.1 Means for effective and adequate lubrication shall be provided when required. Lubricating points shall be readily

accessible, and the pulper shall be lubricated with the proper amount of lubricant prior to delivery.

11. Finish Requirements

11.1 The pulpers shall be treated and painted in accordance with the manufacturer’s standard practice. All surfaces of the machine, other than corrosion-resisting materials, shall be protected against corrosion in the use environment and shall present a neat appearance.

12. Performance Requirements

12.1 The pulper and waterpress assemblies shall meet the capacity requirements given in Table 2 and shall not leak when tested at 125 % of the manufacturer’s recommended supply line pressure.

12.2 *Performance*—See Table 2.

13. Test Methods

13.1 *Significance*—The purpose of this test is to demonstrate the ability of the unit to meet the capacity requirements and to insure that there is no leakage during operation.

13.2 *Procedure*—The machine shall be tested at full load capacity in accordance with manufacturer’s operating instructions. The machine shall function as intended without interruption or malfunction.

13.3 *Performance Profiles*—A new standard is to be developed for energy consumption, water consumption, and productivity profiles.

14. Certification

14.1 Certification of compliance with the standards cited in this specification shall be provided to the purchaser if required

TABLE 2 Performance Requirements

Type Pulper with Waterpress Pulper Diameter Size Inches— Maximum	A		B	
	24	30	24	30
Food Service Capacity lbs/hr	700	900	700	900
Document Destruction Capacity lbs/hr	300	500	N/A	N/A
General Waste Capacity lbs/hr	500	700	N/A	N/A
50 % Paper or News Print and Balance				
General Food Waste Capacity lbs/hr	525	725	525	725

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).

in the purchase document.

14.2 *UL Listing*—Acceptable evidence of meeting the requirements of UL shall be UL Listing, or UL Label, or a certified test report from a recognized independent testing laboratory, acceptable to the user.

15. Product Marking

15.1 *Machine Identification*—Identification shall be permanently and legibly marked directly on the pulper or on a corrosion-resisting material securely attached to the machine at the source of manufacture. Identification shall include the manufacturer’s model, serial number and name, and trademark to be readily identifiable. In addition, information required by UL shall be included on the data plate.

15.2 *Instruction Plate*—An instruction plate of corrosion-resisting material shall be attached to each machine and be visible to the operator.

16. Machine Manuals

16.1 The following information shall be supplied in the manuals:

- 16.1.1 Installation instructions,
- 16.1.2 Operating guide,
- 16.1.3 Maintenance and service procedures, and,
- 16.1.4 Service parts list.

16.2 Manuals shall be in accordance with Specification F 760.

17. Packaging and Packing Materials

17.1 The pulper and waterpress shall be packaged and packed in accordance with Practice D 3951.

18. Quality Assurance

18.1 Unless otherwise specified in the contract or purchase order, the manufacturer is responsible for the performance of all requirements as specified in the contract or order. The manufacturer may use his own or any other facility suitable for the testing of the machine requirements specified herein.